



750°F GRAY RTV SILICONE GASKET MAKER

x'traseal®

SAFETY DATA SHEET

REV: 06

Date: 30 April 2024

1. Product & Company Identification

Product Details

Product name: 750° F Gray RTV Gasket Maker
Physical form: Paste
Odour: Oxime Odour
CAS No.: Mixture

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545 / + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2

Hazard Statement

H315 - Causes skin irritation.

H319 - Causes serious eye irritation

Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



x'traseal®

SAFETY DATA SHEET

750°F GRAY
RTV SILICONE GASKET MAKER

REV: 06

Date: 30 April 2024

P337 + P313 - If eye irritation persists: Get medical advice/attention.

Precautionary Statement – Storage

No precautionary statement

Precautionary Statement – Disposal

No precautionary statement

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Methyl Tri(Methylethylketoxime) Silane	22984-54-9	1 – 8 %
Vinyl Tri(Methylethylketoxime) Silane	2224-33-1	1 – 5 %
Treated Fume Silica	68583-49-3	5 – 15 %
Silicone Polymer	70131-67-8	70 – 80%

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion:

In case of skin contact:

In case of eyes contact:

Seek medical advice immediately.

Wipe with paper towel and immediately clean with water and soap.

Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media:

Unsuitable extinguishing media:

Hazardous decomposition:

All standard fire-fighting media.

Unknown

Carbon dioxide, carbon monoxide, silicone dioxide, nitrogen oxides and formaldehyde.

6. Accidental release measures

Methods for cleaning up:

Take up mechanically.

7. Handling and Storage

Handling:

Protection against fire/ explosion:

Storage:

Cautions:

Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.

General rules of fire prevention should be observed.

Keep container tightly closed and dry.

Extreme heavy in drum form if product packed in 200L drum.



MOHM CHEMICAL SDN. BHD. (REG NO 276851-U)
No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor,
Malaysia. Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919
Website: www.xtraseal.com Email: info@mochem.com



750°F GRAY RTV SILICONE GASKET MAKER

x'traseal®

SAFETY DATA SHEET

REV: 06

Date: 30 April 2024

8. Exposure control / Personal protection

Ingredients with limited values to be controlled:	Not indicated.
Local exhaust:	Recommended
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/protective glasses.
Flammability:	Combustible
Note: Until more data is known, exposure levels should be maintained as low as achievable.	

9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	1.02 ± 0.02
Colour:	Clear and pigmented
Viscosity:	Not indicated
Odour:	Oxime.
VOC content (USEPA Method 24):	< 4 % (as per USEPA Method 24)
Solubility in water:	Insoluble
Boiling point:	Not Applicable
Flash point:	Not Applicable
Ignition temperature:	Not Applicable
Vapour pressure:	Not Applicable

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	None known.
Conditions to be avoid:	None known.
Dangerous reactions:	None known.
Dangerous products of decomposition:	Ketoxime during curing.

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect,	
On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	Until more data is known, exposure levels should be maintained as low as achievable.



750°F GRAY RTV SILICONE GASKET MAKER

x'traseal®

SAFETY DATA SHEET

REV: 06

Date: 30 April 2024

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

For cured sealant landfill may be suitable.
 With respect to local regulation, dispose to suitable incineration plant.

14. Transport Information

Proper shipping name: **Silicone Sealant**
 Hazard technical name: **Not available.**
 Hazard class: **Not available.**

No dangerous goods under the transport regulation.

15. Regulatory Information

Labelling (EC): This product is not subject to the labelling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of SDS ***